

INDEX TO AUTHORS OF PAPERS TO VOLUME 8

- Abdel-Rahman, T. M. and Elbestawi, M. A.** Design of a compact statically balanced direct-drive manipulator, 347–353
- Chang, C., Chung, M. J. and Bien, Z.** Collision-free motion planning for two articulated robot arms using minimum distance functions, 137–144
- Chen, J. S. and Meng, C. H.** Modelling and adaptive control of a flexible one-link manipulator, 339–345
- Cho, D.** Certainty grid representation for Robot Navigation by a Bayesian Method, 159–165
- Cho, H. S. R & D at the Laboratory for Control Systems and Automation of The Korea Advanced Institute of Science and Technology,** 333–338
- Frost, A. R.** Robotic milking: a review, 311–318
- Gardner, J. F., Srinivasan, K. and Waldron, K. J.** Closed loop trajectory control of walking machines, 13–22
- Gordon, J. L., Williams, D. and Hobson, C. A.** Deriving complex location data from simple movement sensors, 151–158
- Gupta, K. C. and Ma, R.** Formulation of manipulator Jacobian using the velocity similarity principle, 81–84
- Harrell, R. C., Adsit, P. D., Munilla, R. D. and Slaughter, D. C.** Robotic picking of citrus, 269–278
- Hemami, A.** Joint velocity uniformity in redundant robot manipulators, 69–72
- Janocha, H. and Schmidt, D.** Requirements for inertial sensor systems for measuring robot positions, 145–150
- Jocković, M., Vukobratović, M. and Ognjanović, Z.** An approach to the modeling of the highest control level of flexible manufacturing cell, 125–130
- Jumarie, G.** Tracking control of flexible robot manipulators with active inertia links, 73–80
- Kassler, M.** Introduction to the special issue on robots and food-handling, 267–268
- Kassler, M.** Robotics and Prawn-handling, 299–301
- Khodabandehloo, K.** Robotic handling and packaging of poultry products, 285–297
- Lee, J. and Bien, Z.** Collision-free trajectory control for multiple robots based on neural optimization network, 185–194
- Lim, T. G., Cho, H. S. and Chung, W. K.** Payload capacity of balanced robotic manipulators, 117–123
- McCloy, D.** Some comparisons of serial-driven and parallel-driven manipulators, 355–362
- McCloy, D.** Step lengths and efficiencies of serial-operated and parallel-operated mechanical legs, 23–29
- Oh, Sang-Rok, Bien, Z. and Hong Sun, H.** A model algorithmic learning method for continuous-path control of a robot manipulator, 31–36
- Pham, D. T., Hu, H. and Pote, J.** A transputer-based system for locating parts and controlling an industrial robot, 97–103
- Pham, D. T. and Nataegh, M. J.** Optimum design of gripper jaws for tapered components, 223–230
- Pierrot, F., Reynaud, C. and Fournier, A.** DELTA: a simple and efficient parallel robot, 105–109
- Pinkava, J.** Towards a theory of sensory robotics, 245–256
- Potkonjak, V.** Distributed positioning for redundant robotic systems, 61–67
- Potkonjak, V. and Krstulović, A.** Improvement of dynamic capabilities of heavy robots, 217–222
- Purnell, G., Maddock, N. A. and Khodabandehloo, K.** Robot deboning for beef forequarters, 303–310
- Rao, T. M. and Arkin, R. C.** 3D Navigational Path Planning, 195–205

- Russell, R. A.** Tactile sensing of 3-dimensional surface features, 111-115
- Sepehri, N., Dumont, G. A. M., Lawrence, P. D. and Sassani, F.** Cascade control of hydraulically actuated manipulators, 207-216
- Siciliano, B.** A closed-loop inverse kinematic scheme for on-line joint-based robot control, 231-243
- Tedford, J. D.** Developments in robot grippers for soft fruit packing in New Zealand, 279-283
- Vernon, D.** A system for robot manipulation of electrical wires using vision, 47-60
- Warnecke, H. J. and Baumeister, K.** Order-picking industrial robot, 37-45
- Weisbin, C. R., Burks, B. L., Einstein, J. R., Feezell, R. R., Manges, W. W. and Thompson, D. H.** HERMIES-III: A step toward autonomous mobility, manipulation and perception, 7-12
- Youlun, X. and Han, D.** Optimization of manipulator dynamics in non-extreme design case, 131-136

